

RDJ
04/30/01

-1-

Date: <u>4.30.01</u>	Express Mail Label No. <u>EL551548231US</u>
----------------------	---

Inventor: Thomas E. Gorsuch
Attorney's Docket No.: 2479.2026-000

WIRELESS COMMUNICATION SYSTEM HAVING MOBILITY-BASED CONTENT DELIVERY

BACKGROUND

5 Demand for wireless communications equipment and services continues to grow at an unprecedented rate throughout the world. Increasingly, such systems are commonly relied upon to provide voice and data communications to a growing sector of the public. While these systems originally depended upon analog signaling technology, there is essentially unanimous agreement that future systems will be based on various types of digital signal coding schemes.

10 The typical wireless communication system is a point-to-multipoint type system in which a central base station communicates with a number of remote units located within a local geographic area of coverage known as a cell. This system provides for duplex communication such that signals may be sent in both a forward direction (from the base station to the remote unit) as well as in a reverse direction (from the mobile
15 remote unit back to the base station). In order to support communication between the remote unit and networks such as the Public Switched Telephone Network (PSTN), or data networks such as the Internet, the wireless system must also provide for various logical components and functional entities.

20 Consider the Code Division Multiple Access (CDMA) and Time Division Multiple Access (TDMA) digital systems presently in widespread use. Each of these systems provides for certain logical types of the radio channels that make up the forward

link and reverse link. In particular, the forward link channels often include a pilot channel, paging channels, and multiple forward traffic channels. The traffic channels are used to carry the payload data between the base station and the mobile unit. A pilot channel is also typically required to allow the remote unit to maintain synchronization
5 with the base station. The paging channels provide a mechanism for the base station to inform the remote unit of control information, such as the assignment of forward traffic channels to particular connections and/or subscriber units.

Likewise, an access channel is provided in the reverse direction in addition to reverse traffic channels. The access channels allow the remote units to communicate
10 control information with the base station, such as to send messages indicating the need to allocate or deallocate connections as required.

Various environmental conditions can affect the performance of any wireless communications system. These elements include atmospheric signal path loss, which may often introduce fading and interference. Fading may include variations that are
15 introduced as a result of the specific terrain within the cell, as well as other types of fading, such as multipath fading, that occurs due to signal reflections from specific features, such as buildings that cause fluctuations in received signal strength. Systems in which the remote unit may be a mobile unit, especially those potentially operating at higher speeds, such as the cellular telephones used in automobiles, are particularly
20 susceptible to multi-path fading. In such an environment, the signal pathways are continually changing at a rapid rate.

A similar impact on performance can result from movement of the subscriber units relative to the base station. Motion can make it difficult for the base station to precisely locate the subscriber unit. In addition, the signal pathways continuously
25 change at a rate proportional to the mobility rate. To maintain a wireless link, additional power and traffic channels may have to be allocated to the moving subscriber. This additional allocation of wireless resources removes resources that would otherwise be available to other subscribers. This negative impact on other subscribers is more acutely

felt during rapid movement and when attempting to maintain high data rates across the wireless link.

SUMMARY

Embodiments of the invention reduce the impact of motion and similar
5 phenomenon on the wireless user community as a whole. The system employs pricing tiers, which represent each subscriber's mobility-based privileges to specific content. That is, a mobile user can be charged a premium to maintain the same quality of service as a stationary user. The impact of mobility is thus felt by the mobile subscriber, either by experiencing reduced bandwidth or through higher subscription fees.

10 A particular embodiment of the invention includes a method of delivering content to a portable wireless device. A wireless communication link is established between a portable device and a base station. The communication link can include a Code Division Multiple Access (CDMA) based protocol.

A mobility state of the portable device is then detected. More specifically, the
15 mobility state is selected from at least three mobility states, including stationary, pedestrian, and mobile.

Based on the detected mobility state, limited content may be transmitted over the communication link. Each mobility state is associated with at least one pricing plan from a plurality of available pricing plans. This can include defining, for each pricing
20 plan, a respective set of deliverable content types based on the mobility state.

In addition, a representation of the deliverable content types can be displayed to a user of the portable wireless transceiver..

Aspects of the invention can be embodied in a computing system for affecting the transmission of content over a wireless communication link. There being a portable
25 wireless transceiver in communication with the wireless communication link. The portable wireless transceiver including an associated level of service and a mobility state. A computer program routine operates on the level of service and the mobility state to affect the rate of data transmitted over the wireless communication link.

The level of service can be based on a pricing plan associated with the portable wireless transceiver. More particularly, the level of service can identify a plurality of allowed content types transmittable over the wireless communication link. Each allowed content type may be identified by a respective service port number, a respective
5 protocol identifier, or a respective file type.

The mobility state can be selected from at least three mobility states. In addition, the mobility state can be computed from a metric associated with the wireless communication link or from mobility data in the portable wireless transceiver.

The computer program routine can determine a disallowed transmission. The
10 computer program routine can then block transmission of the disallowed transmission over the wireless communication link.

A more particular communication system includes a wireless base station transceiver and a portable wireless transceiver in communication over a wireless link. A computer can be coupled to the portable wireless transceiver. The portable wireless
15 transceiver can have an associated pricing plan. Data can be transmitted between the transceivers over the wireless link.

In addition, a mobility processing routine in the base station can store a mobility state for the portable wireless transceiver. The mobility state can be computed by a processor in the base station. In particular the mobility state can be computed from data
20 derived from the performance of the wireless communication link or from data provided by the portable wireless transceiver.

A content filter can also be included for blocking data from transmission over the wireless link based on the pricing plan and the mobility state. The content filter can further block data based on a content type associated with the data. The content type
25 can be represented by a service port number, a message protocol, or a file type.

A gateway can also be disposed between the base station and a wide area network. The gateway can include the content filter.

BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing and other objects, features and advantages of the Wireless Communication System Having Mobility-Based Content Delivery will be apparent from the following more particular description of embodiments of the invention, as illustrated
 5 in the accompanying drawings in which like reference characters refer to the same parts throughout the different views. The drawings are not necessarily to scale, emphasis instead being placed upon illustrating the principles of the invention.

Fig. 1 is a block diagram of a particular communication system suitable for practicing embodiments of the invention.

10 Fig. 2A is a block diagram of a particular forward wireless link 240.

Fig. 2B is a block diagram of a particular reverse wireless link 260.

Fig. 3 illustrates an example service rights table of FIG. 1.

Fig. 4 is a block diagram of Internet protocols in the OSI architecture model.

Fig. 5 is a schematic diagram of the mobility database of FIG. 1.

15 Fig. 6 is a flowchart of a particular mobility state processing routine.

Fig. 7 is a flowchart of a particular packet processing routine.

DETAILED DESCRIPTION

Fig. 1 is a block diagram of a particular communication system suitable for practicing embodiments of the invention. As shown, one or more network servers 2 are
 20 in communication with a Wide Area Network (WAN), such as the Internet 5. Each network server 2 typically includes a data store 3 for storing information content 4. The network servers 2 communicate and exchange information with remote clients over the network 5. To that end, the network servers 2 can include a Web server for providing Web-based content to an end-user.

25 The communication system 1 interfaces to the WAN 5 through one or more gateway processors 10. Each gateway 10 typically includes a firewall 11 for protecting the communication system 1 from unauthorized packets and a router or switch for directing messages to and from one or more base stations 20. The gateway 10 can also

route messages to and from a local network server 2' having a content database 3' that stores content 4', and a data server 18 having a database or data warehouse 19 that stores data such as a service rights database 100 (discussed in detail below) and a mobility database 190 (discussed in detail below).

- 5 Each base station 20 includes a base station processor 21 controlling a wireless transceiver 23 for communicate with a plurality of subscriber access units (SAU) 30 over a wireless communications link. For illustrative purposes, only a single subscriber access unit 30 having a wireless communication link 25 is shown. The wireless communications link 25 includes a forward link 24 from the base station 20 to the
- 10 subscriber access unit 30 and a reverse link 26 from the subscriber access unit 30 to the base station 20.

- The subscriber access unit 30 is portable and includes a subscriber processor 31 for controlling a wireless transceiver 33 for communicating over the wireless link 25. The subscriber access unit 30 can be in communication with a computing device 40,
- 15 such as a laptop computer, a desktop computer, a personal digital assistant, an Internet appliance, or another suitable device. It should be recognized by those of ordinary skill in the art that the subscriber access unit 30 and computing device 40 can be integrated into a single package, such as an Internet-enabled telephone. It should also be recognized that the subscriber access units 30 need not be identical.

- 20 The communication system 1 is a demand access, point-to-multipoint wireless communication system. That is, the computers 40 can transmit data to and receive data from the network servers 2, 2' through bidirectional wireless connections implemented over the forward links 24 and the reverse links 26. It should be understood that in a point-to-multipoint multiple access wireless communication system 1 as shown, a given
- 25 base station 20 typically supports communication with a number of different subscriber access units 30, in a manner that is similar to a cellular telephone communication network.

 Also, as noted above, the gateway 10 can be in communication with a plurality of base stations 20. It should be recognized by one of ordinary skill in the art that each

base station 20 can interface to the WAN 5 through a respective gateway 10. In that case, the plurality of gateways 10 can employ tunneling protocols to exchange subscriber data as a subscriber access unit 30 transitions from one base station to another base station.

5 In accordance with a particular embodiment of the invention, the wireless communications link 25 adheres to a standard digital wireless protocol, such as Code Division Multiple Access (CDMA) based protocols. The techniques described herein can also be applied to other wireless protocols, including Time Division Multiple Access (TDMA) based protocols. Those of ordinary skill in the art should recognize
10 that other standard protocols or proprietary protocols may also be used in practicing the invention.

Fig. 2A is a block diagram of a particular forward wireless link 240. In accordance with CDMA technology, the forward link includes a pilot channel 242, a paging channel 244, and a plurality of forward traffic channels 246-1,..., 246-N. The
15 base station 20 assigns forward traffic channels 246 to a subscriber access unit 30 based on quality of service parameters. In particular, a subscriber access unit 30 may require an increasing number of forward traffic channels 246 to maintain a desired bit rate.

Fig. 2B is a block diagram of a particular reverse wireless link 260. In accordance with CDMA technology, the reverse link includes an access channel 262 and
20 a plurality of reverse traffic channels 266-1,..., 266-M. As with the forward traffic channels 246, the number of reverse traffic channels 266 may depend on a desired bit rate.

In a CDMA architecture, assigning more channels to a particular subscriber access unit 30 reduces the resources available to other subscriber access units. This can
25 degrade the quality of service provided to the other users. One occasion where a subscriber access unit may request additional traffic channels is in a mobile environment. As a subscriber access unit 30 moves, it becomes harder for the stationary base station 20 to provide data to the subscriber access unit 30. The base station, to compensate, may increase power and assign additional traffic channels to the wireless

communications link 25. A stationary subscriber access unit 30, in comparison, may achieve an identical data rate while consuming lower power and fewer traffic channels. It is desired that the base station 20 not penalize stable or more stationary subscribers in order to serve one or more mobile units. It should be noted, however, that even
5 stationary subscribers can appear to be mobile to the base station due to various electromagnetic interferences that may be local to the stationary subscriber access unit 30 or in the path of the wireless link 25.

In accordance with embodiments of the invention, a subscriber's quality of service can depend on a pricing plan or level. That is, a mobile user can be charged a
10 premium to maintain the same quality of service as a stationary user. In accordance with a particular embodiment of the invention, three mobility levels are defined: stationary, pedestrian, and mobile. The definitions and technical distinctions between the three mobility levels are an engineering choice based on the particulars of the host wireless communications system. Similarly, details on the pricing plan are largely an
15 engineering and marketing choice based on the technical parameters of the communications system and the demographics of the customer base.

Fig. 3 illustrates an example service rights table. As shown in the table 100, there are three columns representing the three defined mobility states 110: stationary, pedestrian, mobile. The rows represent the available pricing plans 120. The table's data
20 fields identify the service rights for the subscriber. In a particular embodiment, the data fields are bit maps of the service rights.

In this simplified example, a subscriber can obtain three tiers of service in the pedestrian and mobile states: full-service, partial service, or no service. For example, at pricing plan II, the subscriber receives full-service while stationary, limited service
25 while operating at pedestrian levels, and no service when fully mobile. The issue then becomes how to divide content across the three mobility states.

In a particular embodiment of the invention, content is provided to the subscriber access unit in accordance with protocols that adhere to the Open Systems Interconnect (OSI) model. More particularly, the communications system 1 adheres to

be TCP/IP standards. The approach to selecting content is thus chosen to follow TCP/IP standards and Internet conventions.

Fig. 4 is a block diagram of Internet protocols in the OSI architecture model. As shown, the OSI architecture 50 includes seven protocol layers: a physical layer 51, a data layer 52, a network layer 53, a transport layer 54, a session layer 55, a presentation layer 56, and an application layer 57. Each layer can include a plurality of protocols. In general, content is exchanged between applications at the application layer 57. For transmission to a receiving application, the content is formatted according to a particular application protocol and encapsulated by lower-level protocols. When received at a destination, the lower level protocols are removed to expose the content. To reduce the size of messages transmitted between network computers, the content is divided into small units and delivered as packets. Across the Internet 5, the packets adhere to the Internet protocol (IP). In practice, the gateway 10 can also communicate with the local network server 2', the data server 18 and the base station using TCP/IP standards.

Because the impact on other subscribers is most acute when wireless resources, such as power and channel allocations, are commandeered by subscribers requesting high data rates over a relatively long period of time, the services provided can be chosen or excluded in response to the requested bandwidth. In such a case, a wireless metric can be chosen as the product of power, channels, and saturation of users in the particular cell. In effect, a subscriber's mobility can be used to impact power and channel allocations to that subscriber based on the service rights table 100.

Such an approach, however, implies knowledge of the payload content in individual packets. Furthermore, the gateway 10 may need to estimate the impact of delivering the packet on other subscribers. These tasks are complicated by the fact that the packets may arrive out of order. It is usually up to the destination host (i.e., the computer 40) to determine whether all packets have been received and the final size of the content payload. Analyzing this data upstream from the destination host adds additional, and possibly redundant, processing to the gateway 10.

5

10

15

20

25

In accordance with a particular embodiment of the invention, the gateway 10 identifies the content as part of its routing or firewall processing. The gateway 10 is then responsible for determining whether or not to deliver the packet to the subscribers respective base station 20. To facilitate this processing, a mobility table 190 is

maintained by the gateway 10 and the base stations 20. The database table 190 is stored in the data warehouse 19 of the data server 18 as a relational database table.

Fig. 5 is a schematic diagram of the mobility database 190. Shown are three fields, a subscriber identification field 192, a pricing plan identifying field 194, and a mobility level identification field 196. For each subscriber, the pricing plan is fixed by a systems administrator so that the pricing data identification field 194 indicates the subscribers chosen pricing plan, as reflected in the service rights table 100. The mobility level is, in contrast, dynamic. The base station currently responsible for a particular subscriber periodically updates the mobility level indication field 196 in the mobility database 190 based on the subscriber access unit's 30 current mobility state.

Fig. 6 is a flowchart of a particular mobility state processing routine. Detection of a user's mobility state can be performed by the base station processor 20. The routine 210 periodically computes a mobility state for each subscriber access unit. Each iteration is initiated by a timer interrupt at step 211.

Any suitable technique can be used to determine the mobility state, including mobility detection at the subscriber access unit 30 (such as from a mercury switch) and data computed from the reverse access channel 262 or reverse traffic channels 266. At step 213, the routine 210 measures mobility metrics specific to the applicable methods employed in the system and the subscriber access unit 30.

From the mobility metrics, the routine computes a mobility state at step 215. Again, the computed state may reflect actual motion of the subscriber access unit or degraded performance due to interference. At step 217, the computed mobility state is stored in the subscriber's mobility field of the mobility table 190.

Because the subscriber may not be moving, the routine 210 can forward messages to the subscriber access unit 30 at step 219 to indicate the current mobility state and service level. This information can be displayed to the subscriber using the computer 40. In particular, an icon 45 (FIG. 1) representing the current mobility state is rendered on the subscriber's computer display 42. The subscriber may select the icon to display details of the current level of service.

Fig. 7 is a flowchart of a particular packet processing routine. Each packet can be processed by the gateway 10 (Fig. 1) during its firewall processing. The packet processing routine 120 begins at step 121, where the mobility state of the destination subscriber access unit 30 is determined. This is accomplished by accessing the mobility table 190 using the subscriber's identification as a key and then fetching the mobility state 196 and pricing plan 194 from the record.

At step 123, the routine 120 looks up the allowed services from the service rights table 100 based on the fetched pricing plan and the mobility state values. The result is an allowed service bitmap.

Once the allowed services are identified, the associated bitmap can be used to filter the content. At step 125, the allowed service bitmap is logically ANDed with the content type from the packet. If the subscriber access unit 30 is allowed to receive this content (AND result is 1), the packet is transmitted over the forward traffic channels to the subscriber access unit at step 127. If, however, the packet cannot be forwarded to the subscriber access unit 30 (AND result is 0), the gateway 10 performs further processing in response to the disallowed packet at step 129.

In response to a disallowed packet, the gateway 10 can queue the packet in the data warehouse 19 for possible later delivery to the subscriber access unit 30. This would involve additional overhead to store and manage the queued data packets.

Another approach more consistent with Internet conventions is to return an Internet control message to the source host of the content advising the source to halt further content delivery. This can be accomplished using, for example, the destination unreachable message in the Internet Control Message Protocol (ICMP). Alternatively, an ICMP squelch message can be sent to the source server 2, 2' to reduce the throughput of the packets to more closely match the wireless bandwidth allocated to the subscriber access unit 30.

Although the packet processing routines 120 has been described as being processed by the gateway 10, the routine may be processed in whole or in part by the base station processor 20 associated with the subscriber access unit 30. In practice,

there is an engineering choice between overburdening the gateway 10 and overburdening the data path between the gateway 10 and the base station processor 20. It is expected that the additional processing in the gateway 10 will not add appreciable latency to the throughput of the content. This is especially true when each base station
5 20 is in communication with a dedicated gateway 10.

The above description of embodiments focuses on the content being forwarded to the subscriber access unit 30. It is appreciated that the system can be adapted to also address requests from the subscriber access unit 30. That is, the base station 20 can drop requests for content that are inconsistent with the subscriber's current service level
10 as determined from the service rights table 100. For example, a mobile level I subscriber cannot, according to the example service rights table 100, receive or request any content. Any HTTP request from the subscriber can therefore be blocked by the base station, without having to wait for the request to be serviced by a server 2, 2' and then blocking the content. Because a subscriber's mobility state can change after the
15 request is sent, the content should still be blockable - regardless of the mobility state at the time the request was sent.

A particular embodiment, therefore, verifies reverse-directed packets (away from the SAU 30) as well as forward-directed packets (toward the SAU 30). More particularly, disallowed service port activity is blocked regardless of the message
20 source. This processing can be consolidated in the gateway 10 and base station 20 nodes.

Limiting forward traffic may be sufficient to maintain an acceptable quality of service for all users. This may be particularly true when the subscriber is web browsing, which only requires the transmission of a short Universal Resource Locator (URL)
25 string over the reverse traffic channels. There are situations, however, when a subscriber attempts to transmit large data files over the reverse traffic channels. An example would be an FTP file transfer.

To preserve the reverse traffic channels, at least a portion of the packet processing routine 120 of Fig. 7 can be replicated on the subscriber access units 30.

Because the service rights are computed at the base station 20 and transmitted to the subscriber access unit 30 for display to the user, that processing should not be required at the subscriber access unit 30.

Referring again to Fig. 7, processing at the subscriber access unit 30 can begin at
5 step 125. There the allowed service bitmap is logically ANDed with the content type from the packet. If the subscriber access unit is allowed to transmit this content (AND result is 1), the packet is transmitted over the reverse traffic channels to the base station at step 127. If, however, the packet cannot be transmitted (AND result is 0), at step 129 the subscriber access unit does not transmit the disallowed packet.

10 Those of ordinary skill in the art should recognize that methods for implementing a Wireless Communication System Having Mobility-Based Content Delivery may be embodied in a computer program product that includes a computer usable medium. For example, such a computer usable medium can include a readable memory device, such as a solid state memory device, a hard drive device, a CD-ROM, a
15 DVD-ROM, or a computer diskette, having computer-readable program code segments stored thereon. The computer readable medium can also include a communications or transmission medium, such as a bus or a communications link, either optical, wired, or wireless, having program code segments carried thereon as digital or analog data signals.

20 While the system has been particularly shown and described with references to particular embodiments thereof, it will be understood by those of ordinary skill in the art that various changes in form and details may be made therein without departing from the scope of the invention encompassed by the appended claims. For example, the methods of the invention can be applied to various environments, and are not limited to
25 the environment described herein. In particular, the communications system 1 is described such that the shared channel resource is a wireless or radio channel. It should be understood, however, that the techniques described herein may be applied to allow shared access to other types of media, such as telephone connections, computer network

	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2423	2424	2425	2426	2427	2428	2429	2430	2431	2432	2
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	---